

TECHNICAL DATA

C-49 ALL PURPOSE CLEANER

C-49 is the most versatile and effective cleaner for fabrics, leather, carpet, plastics, laminates and even metals; in other words, for cleaning all types of surfaces generally found in commercial & private aviation, building or institutional interiors, RV, truck and marine interiors, or even home interior. C-49 has a pleasant, clean smell and is safe for users and all interior surfaces. Extremely easy to use, and is supplied in concentrate so dilution can be varied for a wide range of soil conditions.

ADVANTAGES

- Cleans plastics, fabrics, carpets, leather, vinyl, stainless steel, finished wood, and even high gloss polyurethane finishes
- Safe and pleasant for users and the environment
- Will not damage paint, plastics, fabrics (including woolens), decorator fabrics, upholstery, finished leather or carpets
- Gentle, effective cleaning and leaves a pleasant fresh aroma
- Safe to plastics, rubber and all metals
- Completely biodegradable
- Hard water stable, cold water efficient
- Supplied in convenient concentrate for dilution for any cleaning need
- Conforms to Airframe OEM standards and specifications

SPECIFICATIONS

- **Appearance:** Clear light amber liquid
- **Odor:** Mild Citrus
- **pH:** 10.2 – 10.5 @ 25°C
- **Solubility:** Infinite in water
- **Flash Point:** None
- **Specific Gravity:** 1.00 @ 25°C



85 JETSON LANE, CENTRAL ISLIP, NEW YORK 11722
516.935.4000 FAX 516.935.4039

WWW.NUVITECHEMICAL.COM
WWW.UNIVERSALPHOTONICS.COM

INSTRUCTIONS FOR USE

Spot cleaning: Dilute Nuvite C-49 1:8 with water. Spray terry towel to dampen cloth, and then apply to soiled spots. Soak out as much soil as possible into dry terry towel. If soil spot persists after soaking with towel, spray C-49 directly on spot and use soft brush to agitate up and down, then side to side. Reapply dry terry towel to soak out agitated residue. Repeat as needed. Finally, lightly spray around general area of spot, and work surface with up and down then side-to-side action with terry towel.

For broad areas: Dilute C-49 to 1:12. Clean soiled area with up/down, then side to side action with C-49 dampened terry towel. As surface becomes wet, switch to dry towel.

For leather: After cleaning very soiled areas with C-49, replace oils and surface condition with Nuvite **Leather Guard**. Always use good ventilation, with eye and skin protection, especially when working beneath surfaces being cleaned.

When using Nuvite products, please use recommended procedures and equipment. For further product information, and technical support, consult a Nuvite Representative at 800.394.8351

HEALTH AND SAFETY

Users should follow good safety procedures, including wearing of gloves and goggles along with other standard safety procedures. Refer to Safety Data Sheet for further health and safety information.

AVAILABILITY

C49 is available in 1oz and 4oz samples, Quart, 1 & 5 Gallon containers or 55 Gallon Drums, and 5000 gallon tank wagons.

This technical data sheet is offered in good faith without warranty or representation solely for the buyer's use in the evaluation of this product. It is the responsibility of the buyer and end user to determine the data and safety information with respect to applicable laws, regulations, and the fitness & character of this product prior to full scale use. UNIVERSAL PHOTONICS and or NUVITE CHEMICAL COMPOUNDS (seller) assumes no legal liability for any injury, accident, loss, or damage through the use of this product of which such uses are beyond seller's control.c49.10.16.td