

TECHNICAL DATA

ELIMINATE

CONCENTRATED LAVATORY HOLDING TANK & SYSTEM CLEANING FLUID

Eliminate is a technology-based method for lavatory system care and ongoing maintenance. Eliminate's concentrated toilet tank flush/soak additive compound is specifically designed to break-up and disperse all hard-to-remove residues, i.e., paper and paper by-products, mineral scale, and any waste by-products commonly found in lavatory holding tanks. It is formulated to be safe to equipment and personnel while effectively dislodging and breaking down common lavatory sludge build-up within the system. In addition, Eliminate's cleaning action will also service both on-board and ground-based internal pump mechanisms to maintain effectiveness and ease of operation for the long haul.

Eliminate is a liquid product that both users and ground-based facilities prefer over powders and fillers that can contribute to system sluggishness and potential clogging due to the instability of such powders. Eliminate users find it very cost effective while finding the process efficient, effective and extremely easy to use.

- Exceptional dispersing and cleaning performance
- Completely biodegradable
- Does not contain any restricted ingredients such as phosphates
- Safe to internal pump systems and all working parts
- Safe to Airport Tritcherator and municipal standards
- Conforms to Airframe OEM standards and specifications
-

PHYSICAL CHARACTERISTICS

- **Appearance:** Dark brown, liquid
- **Odor:** Mild
- **pH:** 11.8 - 12.5 at 25°C
- **Solubility:** Completely soluble in water
- **Flash Point:** None
- **Specific Gravity:** 1.02 at 25°C



85 JETSON LANE, CENTRAL ISLIP, NEW YORK 11722

516.935.4000 FAX 516.935.4039

WWW.NUVITECHEMICAL.COM

WWW.UNIVERSALPHOTONICS.COM

INSTRUCTIONS FOR USE

1. Empty lavatory holding tank. Service with Nuvite Eliminate concentrate undiluted, as received. Allow up to several hours contact time for soaking. Flush all toilet compartments several times during process to re-distribute chemical contact to flushings, shrouds and pump.

Note: If toilets are severely clogged or have not been routinely maintained, utilize an overnight soak procedure and flushing toilets several times during the process. Once routine cleaning soaks are established, an Eliminate program may be used with dilution strength of up to 3 parts water depending on the extent of residual buildups.

2. Remove waste contents from holding tank. For additional odor control and waste removal flush and drain holding tank with a mix solution of **GoodBye-NF** lavatory fluid at 1/2oz per gallon or 1:256 parts of water directly into waste tank. Flush all toilets to circulate for service ready status.

When using Nuvite products, please use recommended procedures and equipment. For further product information, and technical support, consult a Nuvite Representative at 800.394.8351

HEALTH AND SAFETY

Users should use standard safety precautions, such as wearing gloves and eye protection along with any other standard safety procedures. Refer to Safety Data Sheet for further health and information.

AVAILABILITY

Eliminate is available in 1 Quart, 1, 5, 55, & 275 gallon container and 5000 gallon tank wagons.

This technical data sheet is offered in good faith without warranty or representation solely for the buyer's use in the evaluation of this product. It is the responsibility of the buyer and end user to determine the data and safety information with respect to applicable laws, regulations, and the fitness & character of this product prior to full scale use. UNIVERSAL PHOTONICS and or NUVITE CHEMICAL COMPOUNDS (seller) assumes no legal liability for any injury, accident, loss, or damage through the use of this product of which such uses are beyond seller's control.eliminate.10.16.td